



FLAME ARRESTORS

www.cashco.com
Innovative Solutions

Get Consistent Quality

By involving every employee in our ISO 9001:2008 Quality Assurance Program, you can count on the quality we provide you. We have coordinated our business systems, invested in state-of-the-art machine tools, and built an extensive component inventory so we can consistently provide cost-effective solutions and on-time delivery to meet your replacement or project requirements — regardless of size or complexity.

Make the Right Choice

"We simply make it right" by putting your needs first. The next time you specify control valves, regulators or vapor control emission systems, or you need a replacement fast...call the supplier that makes it right. Rely on Cashco for your single-source convenience. Great service, field-proven quality, and timely delivery makes Cashco the right choice.

Select Control Valves & Regulators FOR SPECIALIZED OR UTILITY SERVICE

We manufacture a broad line of throttling rotary and linear control valves, pressure reducing regulators, and back pressure regulators in line sizes from 1/4 inch to 10 inches and Cv ranges from .002 to 4,406. Models are available to handle slurries, cryogenic service, and corrosive fluids; to withstand high temperatures and pressures; and to maximize the reduction of fugitive emissions. Contact Cashco for complete product information.

WE ARE CASHCO

The Strength Of Our Organization Is Our Employees

COMMITMENT. QUALITY. DEDICATION.

Cashco, Inc. is a manufacturing enterprise, centrally located within the United States. Our employees use hard work, commitment, and passion to define company goals that deliver world-class products at a fair price.

At Cashco, we continue to innovate our products until they are recognized as best in class within their respective industry. If the customer is not satisfied, we take it upon ourselves to make it right. Cashco employees are the bloodline of our company elevating products above industry standards for performance, dependability, and safety.

At Cashco, the strength of our organization is our employees.

TABLE OF CONTENTS

Flame Arrestors

Deflagration

Model 6A00	4
Model 6A00-EM	5
Model 6A00-HT	6
Models 6B00	7
Model 6C00	8
Model 6E00	9
Model 6K00	10
Model 6ZA21	11

Detonation

Model 7A00	12
Model 7A00-S	13
Model 7C00	14
Model 7J00	15

MODEL // 6A00

The Model 6A00 is an inline deflagration flame arrestor. The primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The element design is bi-directional and available for horizontal or vertical installations.



VIEW IN 3D!

LINE SIZES AVAILABLE



3/4" (DN20)	1" (DN25)	1.25" (DN32)	1.5" (DN40)	2" (DN50)	2.5" (DN65)	3" (DN80)	4" (DN100)
5" (DN125)	6" (DN150)	8" (DN200)	10" (DN250)	12" (DN300)	14" (DN350)	16" (DN400)	



EXPLOSION GROUPS

IIA1	IIA	IIB1	IIB3	IIB	IIC
------	-----	------	------	-----	-----



END CONNECTIONS

Rp	BSPP	NPT	DIN (PN10)	ASME (150#RF)
----	------	-----	---------------	------------------

The Model 6A00 is designed, manufactured, and tested according to Directive 2014/34/ EU (ATEX114) and ISO 16852.



COMMON APPLICATIONS

OIL & GAS INDUSTRY PIPING, CHEMICAL PROCESSING PLANTS, POWER GENERATION FACILITIES, WASTEWATER TREATMENT PLANTS, MARINE & OFFSHORE APPLICATIONS

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6A00-EM

The Model 6A00 inline deflagration flame arrestor is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6A00 is used as an independent safety system to ensure explosion protection.



LINE SIZES AVAILABLE



2" (DN50)	2.5" (DN65)	3" (DN80)	4" (DN100)	5" (DN125)	6" (DN150)
8" (DN200)	10" (DN250)	12" (DN300)	14" (DN350)	16" (DN400)	



EXPLOSION GROUPS

IIA1	IIA
------	-----



END CONNECTIONS

DIN (PN10)	ASME (150#RF)
---------------	------------------



COMMON APPLICATIONS

REFINERIES & PETROCHEMICAL PLANTS, CHEMICAL PROCESSING PLANTS, POWER GENERATION PLANTS, WASTEWATER TREATMENT PLANTS, MARINE & OFFSHORE APPLICATIONS


The Model **6A00** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6A00-HT

The Model 6A00-HT is a high temperature, inline deflagration flame arrestor that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6A00 is used as an independent safety system to ensure explosion protection.



LINE SIZES AVAILABLE



3/4" (DN20)	1" (DN25)	1.25" (DN32)	1.5" (DN40)	2" (DN50)	2.5" (DN65)	3" (DN80)	4" (DN100)
5" (DN125)	6" (DN150)	8" (DN200)	10" (DN250)	12" (DN300)	14" (DN350)	16" (DN400)	



EXPLOSION GROUPS

IIA1	IIA	IIC
-------------	------------	------------



END CONNECTIONS

Rp	BSPP	NPT	DIN (PN10)	ASME (150#RF)
-----------	-------------	------------	----------------------	-------------------------



COMMON APPLICATIONS

REFINERIES & PETROCHEMICAL PLANTS, OIL & GAS TRANSMISSION PIPELINES, POWER GENERATION FACILITIES, CHEMICAL MANUFACTURING, WASTEWATER TREATMENT PLANTS

The Model **6A00** is designed, manufactured, and tested according to Directive 2014/34/ EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6B00

The Model 6B00 inline deflagration flame arrestor is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6B00 is used as an independent safety system to ensure explosion protection.



**VIEW IN
3D!**

LINE SIZES AVAILABLE



1.5" (DN40)	2" (DN50)	3" (DN80)	4" (DN100)
5" (DN125)	6" (DN150)	8" (DN200)	



EXPLOSION GROUPS

IIA1	IIA
-------------	------------



END CONNECTIONS

DIN (PN10)	ASME (150#RF)
----------------------	-------------------------



COMMON APPLICATIONS

OIL & GAS PIPELINE INSTALLATIONS, CHEMICAL PROCESSING PLANTS, REFINERY PROCESS PLANTS, INDUSTRIAL COMBUSTION SYSTEMS, WASTEWATER TREATMENT PLANTS

*The Model **6B00** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.*

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6C00

The Model 6C00 end-of-line flame deflagration and endurance burn proof flame arrestor is a device that can be fitted directly on a vessel, tank vent nozzle, or on the end of a vent line. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame from the outside. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6C00 is used as an independent safety system to ensure explosion protection.



LINE SIZES AVAILABLE

1.5" (DN40)	2" (DN50)
-----------------------	---------------------



EXPLOSION GROUPS

IIA



END CONNECTIONS

DIN (PN10)	ASME (150#RF)
----------------------	-------------------------



COMMON APPLICATIONS

FUEL STORAGE & DISTRIBUTION, INDUSTRIAL HEATING EQUIPMENT, CHEMICAL PROCESS VENTING SYSTEMS, BIOGAS AND LANDFILL GAS RECOVERY SYSTEMS, VENTILATION SYSTEMS IN HAZARDOUS ENVIRONMENTS

The Model 6C00 is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6E00

The Model 6E00 end-of-line deflagration flame arrestor is a device that can be fitted directly on a vessel, tank vent nozzle, or on the end of a vent line. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame from the outside. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6E00 is used as an independent safety system to ensure explosion protection.



**VIEW IN
3D!**

LINE SIZES AVAILABLE



3/4" (DN20)	1" (DN25)	1.25" (DN32)	1.5" (DN40)	2" (DN50)	3" (DN80)
4" (DN100)	6" (DN150)	8" (DN200)	10" (DN250)	12" (DN300)	



EXPLOSION GROUPS

IIB3	IIC
-------------	------------



END CONNECTIONS

Rp	BSPP	NPT	DIN (PN10)	ASME (150#RF)	JIS (10K)
-----------	-------------	------------	----------------------	-------------------------	---------------------



COMMON APPLICATIONS

STORAGE TANK VENTING, OIL & GAS PIPING SYSTEMS, PETROCHEMICAL PROCESSING, INDUSTRIAL COMBUSTION SYSTEMS, OFFSHORE & MARINE APPLICATIONS

The Model **6E00** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6K00

The Model 6K00 Pressure/Vacuum Vent with Flame Arrestor is designed for use on atmospheric and low-pressure storage tanks where pressure and vacuum relief is required. The design includes a deflagration flame arrestor consisting of a crimped SST metal element which allows the flow of gases or vapor of flammable liquids but prevent the flame-transmission from the outside. It provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6K00 is used as an independent safety system to ensure explosion protection.



**VIEW IN
3D!**

LINE SIZES AVAILABLE



2" (DN50)	3" (DN80)	4" (DN100)	6" (DN150)	8" (DN200)
10" (DN250)	12" (DN300)			



EXPLOSION GROUPS

IIB3



END CONNECTIONS

DIN (PN10)	ASME (150#RF)
----------------------	-------------------------



COMMON APPLICATIONS

STORAGE TANK PROTECTION, OIL & GAS PROCESSING, CHEMICAL MANUFACTURING, MARINE & OFFSHORE APPLICATIONS, PETROCHEMICAL PLANTS

The Model **6K00** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 6ZA21

The Model 6ZA21 in-line deflagration flame arrestor is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 6ZA21 is used as an independent safety system to ensure explosion protection.



LINE SIZES AVAILABLE



3/4"
(DN20)

1"
(DN25)

1.5"
(DN40)

2"
(DN50)

EXPLOSION GROUPS



IIA1

IIA

END CONNECTIONS



Rp

COMMON APPLICATIONS



CHEMICAL PROCESSING PLANTS, FUEL GAS SYSTEMS, INDUSTRIAL FURNACES & BOILERS, VENTILATION & EXHAUST SYSTEMS, BIOGAS & LANDFILL GAS SYSTEMS

The Model **6ZA21** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

MATERIALS:

CS or SST

ELEMENT:

SST Material

MODEL // 7A00

The Model 7A00 detonation flame arrestor is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The Model 7A00 is used as an independent safety system to ensure explosion protection.



VIEW IN
3D!

LINE SIZES AVAILABLE



3/4" (DN20)	1" (DN25)	1.25" (DN32)	1.5" (DN40)	2" (DN50)	2.5" (DN65)	3" (DN80)	4" (DN100)
5" (DN125)	6" (DN150)	8" (DN200)	10" (DN250)	12" (DN300)			

EXPLOSION GROUPS



IIA	IIB3	IIC
------------	-------------	------------

END CONNECTIONS



Rp	BSPP	NPT	DIN (PN10)	ASME (150#RF)
-----------	-------------	------------	----------------------	-------------------------

COMMON APPLICATIONS



OIL & GAS PIPELINES, CHEMICAL PROCESSING, STORAGE
TANK VENTING, POWER GENERATION, WASTEWATER
TREATMENT PLANTS

The Model **7A00** is designed, manufactured, and tested according to Directive 2014/34/ EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 7A00-S

The Model 7A00-S detonation flame arrestor is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 7A00-S is used as an independent safety system to ensure explosion protection.



**VIEW IN
3D!**



LINE SIZES AVAILABLE

1/8"
(DN6)

1/4"
(DN8)

3/8"
(DN10)

1/2"
(DN15)



EXPLOSION GROUPS

IIA1

IIA

IIB3

IIC



END CONNECTIONS

Rp

BSPP

NPT



COMMON APPLICATIONS

LABORATORY EQUIPMENT, GAS CHROMATOGRAPHY, MEDICAL DEVICES, INSTRUMENTATION SYSTEMS, FUEL CELLS


The Model **7A00-S** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

HOUSING MATERIALS:
SST

TRIM MATERIALS:
SST

MODEL // 7C00

The Model 7C00 unstable/overdriven detonation flame arrestor type II is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame.



**VIEW IN
3D!**

LINE SIZES AVAILABLE



2" (DN50)	3" (DN80)	4" (DN100)	6" (DN150)
8" (DN200)	10" (DN250)	12" (DN300)	



EXPLOSION GROUPS

D



END CONNECTIONS

ASME (150#RF)



COMMON APPLICATIONS

MARINE VESSEL FUEL SYSTEMS, OIL & GAS OFFSHORE PLATFORMS, CHEMICAL PROCESSING PLANTS, PETROLEUM REFINERIES, CHEMICAL TANKER TRUCKS & RAILCARS

The Model 7C00 is designed, manufactured, and tested according to Title 33, Code of Federal Regulations (CFR), part 154, Appendix A for USCG approved application.

MATERIALS:
CS or SST

ELEMENT:
SST Material

MODEL // 7J00

The Model 7J00 unstable detonation flame arrestor is a device that can be fitted to the opening of an enclosure or to the connecting pipe work of a system of enclosures. Its primary function is to allow the flow of gases or vapor of flammable liquids through the enclosure, but prevent the transmission of a flame. The element inside the housing provides an extinguishing barrier to the ignited vapor mixture by absorbing heat from the flame. The Model 7J00 is used as an independent safety system to ensure explosion protection.



LINE SIZES AVAILABLE



1.5"
(DN40)

2"
(DN50)

2.5"
(DN65)

3"
(DN80)

4"
(DN100)

EXPLOSION GROUPS



IIA

IIB3

END CONNECTIONS



Rp

BSPP

NPT

DIN
(PN10)

ASME
(150#RF)

COMMON APPLICATIONS



OIL & GAS PIPELINES, CHEMICAL PROCESSING PLANTS,
REFINERY PROCESS UNITS, STORAGE TANK VENTING,
WASTEWATER TREATMENT FACILITIES

The Model **7J00** is designed, manufactured, and tested according to Directive 2014/34/EU (ATEX114) and ISO 16852.

MATERIALS:
CS or SST

ELEMENT:
SST Material



Check out the other high quality product lines
available exclusively from **Cashco.**



**Vapor Control
Products**



**Control
Valves**



**Industrial
Regulators**



**Sanitary Regulators
& Control Valves**



**Valve
& Automation**
Total Valve & Control Solutions®

JOHANNESBURG
Tel: 011 397 2833

DURBAN
Tel: 031 579 2593

South Africa:
0861 103 103

E-mail: sales@valve.co.za
www.valve.co.za

